

# GV-650 Video Capture Card



GV-650 D-Type PCI



GV-650 D-Type PCI-E



## Specifications

Input Type	GV-650 D-Type: DB15 X 2
Video Input(s)	4, 8, 12, 16 Cams
Audio Input(s)	2 Channels
Total Recording Rate At 320 X 240 Resolution	60 fps (NTSC), 50 fps (PAL)
Display Rate	60 fps (NTSC), 50 fps (PAL)
Video Resolution - NTSC/PAL	Full D1, Half D1, CIF
Compression Format	Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2
GV-A16 Support	Yes
GV-NET Card Support	Yes
GV-NET/IO Card Support	Yes
Dimensions (W x H)	GV-650 D-Type(PCI & PCI-E) : 144 x 98 (mm) / 5.67 x 3.86 (in)
Installation Guide	<a href="#">D-Type (PCI-E)</a> <a href="#">Installing two cards</a>

**Note:** GV-650 is currently not compatible with VIA series and ATI series chipset motherboards.

### Minimum System Requirements For One Card

OS Supported	32-bit	Windows XP / Windows Vista / Windows 7 / Windows Server 2008
	64-bit	Windows 7 / Windows Server 2008
CPU	Pentium 4-2.4 GHz with Hyper-threading	
RAM	Windows XP: 2 x 512 MB Dual Channels Windows Vista / 7 / Server 2008: 2 x 1 GB Dual Channels	
HDD	80 GB	
VGA	ATI Radeon X600 NVIDIA 6200	
DirectX	9.0c	

### Minimum System Requirements For Two Cards

OS Supported	32-bit	Windows XP / Windows Vista / Windows 7 / Windows Server 2008
	64-bit	Windows 7 / Windows Server 2008
CPU	Pentium 4-2.8 GHz with Hyper-threading	
RAM	2 x 1 GB Dual Channels	
HDD	160 GB	
VGA	ATI Radeon X600 NVIDIA 6200	
DirectX	9.0c	