








Comparison on GV-POE Switch

Models		GV-POE0400	GV-POE0800	GV-POE0801	GV-POE1601	GV-POE2401
Features						
Port	at full 15.4W (IEEE 802.3af)	4	8	8	16	24
	at full 30W (IEEE 802.3at)	2	4	4	8	13
Gigabit RJ-45 Port		0	0	1	2	2
SFP Port		0	0	1	2	2
Power Budget		70W	130W	130W	250W	400W
Dimensions (H x W x D)		24 x 130 x 98 mm (0.9" x 5.1" x 3.9")	44 x 266 x 160 mm (1.7" x 10.5" x 6.3")		44 x 440 x 332 mm (1.7" x 17.3" x 13.1")	
Weight		0.76 kg (1.68 lb)	1.6 kg (3.53 lb)	1.8 kg (3.97 lb)	4.2 kg (9.26 lb)	4.7 kg (10.36 lb)
Operating Temperature		0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 45°C (32°F ~ 113°F)		0°C ~ 40°C (32°F ~ 104°F)	
Web Management		No	No	Yes	Yes	Yes

Note:

- Specifications are subject to change without notice.
- With GV-POE1601/2401, for the usage of RJ-45 Gigabit Ethernet and Gigabit SFP ports, you can only choose one port from group 1 (25TX and 25FX) and one port from group 2 (26TX and 26FX) to connect. Both groups offer one of their ports for connections at a time.